



## Swiftpro™ K30 Single Sided Retransfer Card Printer

Swiftpro provides market-leading solutions with an extensive range of retransfer desktop solutions to meet the needs of the customer and by adding value to global businesses. Our mission is to revolutionize business identity and access management by building trusted partnerships through our simple SMART™ partner distribution networks.

The Swiftpro K30 retransfer card printer has an outstanding print quality for single-sided printing and is upgradeable to double-sided printing. With 300dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalized physical and logical access management.

The ultra-fast, powerful Swiftpro K30 printer is available with contact and contactless smart card encoding technologies and 100-card input and output hoppers, with an optional 250-card input hopper upgrade. This reliable and durable printer is the ideal solution for both entry level to advanced secure card programs for a range of vertical markets.

Selecting the right printer is important. Equally if not more important is using Genuine Swiftpro Supplies. They are critical to delivering printer reliability, print quality and vibrant colors for your card programs. Swiftpro supplies deliver consistency and ensure the longevity of your printer and print head and minimize downtime and create efficiencies in your card programs. Always ask for Genuine Swiftpro Supplies from your Authorized Premiere Value Added Distributor, Premiere Enterprise Solution Provider or Premiere Value-Added Reseller.



### SECURITY

The ribbon erase function prevents leakage of personal information on the monochrome black panel ink ribbon. It scrambles information beyond recognition to protect this data.



### VERSATILITY

Swiftpro's modular design permits customers to upgrade as their card programs need changes.



### IMAGE QUALITY

High Resolution printing using 300 dpi printing provides superior print quality for all your card programs.



### RELIABILITY

Swiftpro K-Series are well respected globally for their Japanese engineering for quality and reliability.




### INNOVATION

Innovating since the 90's with state of the art retransfer printers, providing safe, secure, and reliable ID card printer solutions to global organizations since 1989.



### DURABILITY

Highly durable printers with industry leading warranties on all our products and lifetime on the print head.



# Swiftpro K30 Single Sided

## Retransfer Card Printer



CORPORATE



EDUCATION



FINANCE



HEALTHCARE



RETAIL



TRANSPORT



GOVERNMENT

### Printing

Dye Sublimation Retransfer

Full Color Retransfer printing

Single Sided Printing

YMCK (single-sided): 30 sec/card, 120 cards/hour

256 Gradation Printing

Over the Edge Printing on CR80, ID-1 Cards

### Standard Features

USB & Ethernet connectivity

100-Card Input Hopper (30mil)

100-Card Output Hopper (30mil)

LCD Panel

300 DPI Print Resolution

36 Month Printer Warranty

Lifetime Printhead Warranty

Microsoft Certified Drivers

Solenoid Electronic Lock for Card Input Hopper

Solenoid Electronic Lock for Supplies / Front Door Housing

Software-controlled Lock/Unlock from Status Monitor

K Ribbon Erase Function

IpSec Security for Secure Data Encryption IPv6 and IPv4

Inline Bend Remedy

MAC Address Forced Printing (UV Panel on Card)

Kensington Lock

### Encoding\*

Contactless Encoder, Omnikey 5127 (iClass, MIFARE and DESFire, Felica)

Contact Encoder (CF-7CRW / Control board)

Contact Encoder (CF-7CCS / IC Contact Station)

### Software Supported

CardPresso

Card Exchange

All Card Personalizations software used through Swiftpro Driver\*

\*check with Software vendor, as some features may be limited for use on Swiftpro Printers

Microsoft® Windows® 7, 8, 10, 11 32bit / 64bit

Microsoft® Windows® Server 2008 R2 (SP1) 64bit

Microsoft® Windows® XP Server 2012 64bit

### Swiftpro Genuine Color Ribbons

YMCK - 1000 Yield

YMCKP Peel Off Ribbon - 750 Yield

YMCKU UV - 750 - Yield

InTM Retransfer Film - 1000 Yield

### Physical Specification

Height 13.19 in (335 mm) Without Card Stacker

Width 13.5 in (343 mm) Without Card Stacker

Depth 12.68 in (322 mm) Without Card Stacker

Weight 29.76 lb (13.5 kg)

### Interface

USB 2.0 (Hi-speed / Full Speed)

Ethernet (100BASE-TX / 10BASE-T)

### Options

Flipper Unit

Magstripe and Contact and Contactless Encoders per descriptions to left

### Electrical

Temperature: 59°F to 86°F (15°C to 30°C)

Humidity: 35% to 70% (YMCK ink, No Condensation)

3.5A (110V system) 1.6A (220V system)

310W (maximum power when all options are installed)

### Card Specification

Card Thickness 10-40mil

Card Size ISO 7810 Format, CR80, ID-1

Card Material: PVC, PC, PET, PET-G

Technology Cards Contact and or Contactless with and Without Mag Stripe

### Safety Standards

Agency Listing: UL, CE, FCC, KC, CCC, CSA

\* Magnetic stripe encoding is available with an upgrade to duplex printing.

# IRIS

RETHINKING IDENTIFICATION

The IRIS Companies

www.irisltd.com

marketing@irisltd.com

(610) 944-8588

901 Park Road, Fleetwood, PA 19522