

The Swiftpro K30D retransfer card printer has an outstanding print quality for single and double sided printing. With 300dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalized physical and logical access management.

distribution networks.

The ultra-fast, powerful Swiftpro K30D printer is available with contact and contactless smart code encoding technologies and 100-card input and output hoppers, with an optional 250card input hopper upgrade. This reliable and durable printer is the ideal solution for both entry level to advanced secure card programs for a range of vertical markets.

Selecting the right printer is important. Equally if not more important is using Genuine Swiftpro Supplies. They are critical to delivering printer reliability, print quality and vibrant colors for your card programs. Swiftpro supplies deliver consistency and ensure the longevity of your printer and print head and minimize downtime and create efficiencies in your card programs. Always ask for Genuine Swiftpro Supplies from your Authorized Premiere Value Added Distributor, Premiere Enterprise Solution Provider or Premiere Value-Added Reseller.

JACOB FAULKNER







IMAGE QUALITY











Printing

Dye Sublimation Retransfer

Full Color Retransfer printing

Single and Double Sided Printing

YMCK (single-sided): 30 sec/card, 120 cards/hour

256 Gradation Printing

Over the Edge Printing on CR80, ID-1 Cards

Standard Features

USB & Ethernet connectivity

100-Card Input Hopper (30mil)

100-Card Output Hopper (30mil)

LCD Panel

300 DPI Print Resolution

36 Month Printer Warranty

Lifetime Printhead Warranty

Microsoft Certified Drivers

Solenoid Electronic Lock for Card Input Hopper

Solenoid Electronic Lock for Supplies / Front Door Housing

Software-controlled Lock/Unlock from Status Monitor

K Ribbon Erase Function

IpSec Security for Secure Data Encryption IPv6 and IPv4

MAC Address Forced Printing (UV Panel on Card)

Kensington Lock

Encoding

Magnetic Stripe ISO High/Low Coercivity Encoder

Contactless Encoder, Omnikey 5127 (iClass, MIFARE and DESFire, Felica)

Contact Encoder (CF-7CRW / Control board)

Contact Encoder (CF-7CCS / IC Contact Station)

Software Supported

CardPresso

Card Exchange

All Card Personalizations software used through Swiftpro Driver*

*check with Software vendor, as some features may be limited for use on Swiftpro Printers

Microsoft® Windows® 7, 8, 10, 11 32bit / 64bit

Microsoft® Windows® Server 2008 R2 (SP1) 64bit

Microsoft® Windows® XP Server 2012 64bit

Swiftpro Genuine Color Ribbons

YMCK - 1000 Yield

YMCKK - 750 Yield

YMCKP Peel Off Ribbon - 750 Yield

YMCKU UV - 750 - Yield

InTM Retransfer Film - 1000 Yield

Physical Specification

Height	13.19 in (335 mm)	Without Card Stacker
Width	13.5 in (343 mm)	Without Card Stacker
Depth	12.68 in (322 mm)	Without Card Stacker
Weight	29.76 lb (13.5 kg)	

Interface

USB 2.0 (Hi-speed / Full Speed)

Ethernet (100BASE-TX / 10BASE-T)

Options

Flipper Unit

Bend Remedy

Electrical

Temperature: 59°F to 86°F (15°C to 30°C)

Humidity: 35% to 70% (YMCK ink, No Condensation)

3.5A (110V system) 1.6A (220V system)

310W (maximum power when all options are installed)

Card Specification

Card Thickness 10-40mil

Card Size ISO 7810 Format, CR80, ID-1

Card Material: PVC, PC, PET, PET-G

Technology Cards Contact and or Contactless with and Without Mag Stripe

Safety Standards

Agency Listing: UL, CE, FCC, KC, CCC, CSA



